



FC-100S/300S

AIR CIRCULATOR UTILITY FAN WITH OSCILLATING FEATURE



XPOWER FC-100S & FC-300S Professional Grade Air Circulator Utility Fan is the ideal fan for whole room air circulation, ventilation, and cooling. Feel the difference of the powerful, focused, and extended air flow that our FC line of fans generate compared to a normal home fan and now even more coverage capabilities with an oscillating feature. Powerful focused airflow gets a boost in range and versatility with the new oscillating feature, giving you 56 degrees of side-to-side coverage. The FC-100S & FC-300S comes ETL / CETL safety certified paired with advanced manufacturing technology that includes XPOWER's 4-speed settings for maximized airflow control and high CFM airflow. This multi-purpose fan is energy efficient and is equipped with advanced air fin guide technology to efficiently provide the multidirectional air movement required in your application. A 6 foot Heavy-Duty Wrap-Around-Cord Design and Grab-N-Go Handle, make transporting a breeze. With the lightweight and compact injection molded housing, the FC-100S & FC-300S brings features and powerful airflow in a perfect package.



XPOWER MANUFACTURE, INC
668 S. 6TH AVENUE, CITY OF INDUSTRY, CA, 91746
PHONE: (626) 285-3301 EMAIL: INFO@XPOWER.COM

WWW.XPOWER.COM

SPECIFICATIONS

- Powerful Focused and Extended Air flow for whole room circulation and cooling
- Oscillating feature to get even more powerful circulation
- Maximized energy efficiency with a rated 1,100 CFM (FC-100S) and 2,100 CFM (FC-300S) of airflow
- Heavy duty 6ft - 10ft Wrap-Around Cord Design
- Unique grill design provides focused airflow up to 100+ Ft.
- 4-speed settings
- Fully assembled, low maintenance and easy operation
- Easy portability with Grab-N-Go Handle
- Manufacturer's 1-year limited warranty
- ETL / CETL safety certified

Model No.	FC-100A	FC-300A
Voltz/Hertz	115V / 60 Hz	115V / 60 Hz
Motor	69 Watts	1/4 HP
Power	0.6 Amps	1 Amps
Rated Airflow	1100 CFM	2100 CFM
Speeds	4 Speed	4 Speed
Cord Length	6 Ft.	10 Ft.
Operating Position	360° Rotation	360° Rotation
Stackable	Yes	Yes
Unit Weight	11.5 Lbs.	15.1 Lbs.
Unit Dimensions (LxWxH)	19 x 14.8 x 8.3 in.	17.1 x 23 x 9.6 in.
Housing	PP	PP
Safety Certifications	ETL / CETL	ETL / CETL
Dual Thermal Protection	Yes	Yes
Pallet Quantity	48 Units	28 Units



Whole Room Circulation



Focus Extended Airflow



Energy Efficient

FEATURES


Specially Designed Air Fin for More Focused Airflow



Oscillation On/Off Switch



4 Speed Control Switch



Wrap Around Cord Storage



145° Tilt Position & 56° Oscillating