



# HIGH STATIC BLOWERS

## Versatile Powerful Inflatable Blowers

From 1/8 HP to 3 HP, XPOWER is the only manufacturer that's offering the most complete line of high-static inflatable blowers in the market. XPOWER can support a wide range of entertainment and advertisement needs, whether it's holiday decorations, finish line arches, or structures.

- Precision Injection-Mold Manufacturing
- Thermal Protection Against Overheating
- Lightweight & Durable Polypropylene Housing
- ETL/CETL Safety Certified for Indoor/Outdoor Use



BR-6



BR-15



BR-35



BR-252A



BR-272A



BR-282A



BR-292A



XPOWER MANUFACTURE, INC  
240 CLARY AVENUE, SAN GABRIEL, CA 91776  
PHONE: (626) 285-3301 EMAIL: INFO@XPOWER.COM

[WWW.XPOWER.COM](http://WWW.XPOWER.COM)

# SPECIFICATIONS

Model No.	BR-6	BR-15	BR-35	BR-252A
Volts/Hertz	120V / 60Hz	120V / 60Hz	120V / 60Hz	120V / 60Hz
Motor	1/8 HP	1/4 HP	1/2 HP	1 HP
Power	0.8 Amps	3.2 Amps	5.5 Amps	9.8 Amps
Static Pressure (H2O)	1.85 in.	5.22 in.	7.83 in.	8.51 in.
Rated Airflow	120 CFM	380 CFM	600 CFM	1000 CFM
Speed	Single	Single	Single	Single
Outlet	2 1/2" x 3 3/4"	3 3/4" ø	4 1/4" ø	3 1/4" ø
Cord Length	6 Ft.	6 Ft.	6 Ft.	6 Ft.
Unit Weight	4 Lbs.	8.8 Lbs.	12.8 Lbs.	16.2 Lbs.
Unit Dimensions	8 x 5.7 x 8.5 in.	12.9 x 8 x 12.2 in.	14.6 x 8.4 x 14.7 in.	15.5 x 11.2 x 16.7 in.
Box Weight	4.6 Lbs.	10.4 Lbs.	15 Lbs.	18.60 Lbs.
Box Dimensions	8.7 x 6.3 x 9.4 in.	13.4 x 13 x 9.3 in.	15.4 x 15.4 x 9.40 in.	17 x 12.5 x 17 in.
Safety Certification	ETL / CETL	ETL / CETL	ETL / CETL	ETL / CETL

Model No.	BR-272A	BR-282A	BR-292A
Volts/Hertz	120V / 60Hz	120V / 60Hz	120V / 60Hz
Motor	1 HP	2 HP	3 HP
Power	8.0 Amps	12 Amps	14 Amps
Static Pressure (H2O)	8.4 in.	12.85 in.	16 in.
Rated Airflow	1000 CFM	1500 CFM	1700 CFM
Speed	Single	Single	Single
Outlet	4 1/2" ø	5 1/4" ø	5 1/4" ø
Cord Length	12 Ft.	12 Ft.	12 Ft.
Unit Weight	21.2 Lbs.	22 Lbs.	30.4 Lbs.
Unit Dimensions	18.5 x 10.6 x 19.9 in.	18.5 x 10.6 x 19.9 in.	18.4 x 10.6 x 19.9 in.
Box Weight	25.4 Lbs.	25.6 Lbs.	33.3 Lbs.
Box Dimensions	20 x 11.2 x 18.5 in.	20 x 11.2 x 18.5 in.	20 x 11.2 x 18.5 in.
Safety Certification	ETL / CETL	ETL / CETL	-

